

Industrial Abrasive Belt Sanders

Baldor offers several options when it comes to industrial belt sanders, fixed and tiltable belts, grinder/sanders and even an adjustable speed sander for increased flexibility. All units come with a base mounted on/off switch. 602E-MT equipped with 2x36" 100 grit belt, all others 2x48" 80 grit belt.



Catalog #602E-MT Catalog #248-151D Catalog #248-181TD Catalog #248-151TD Catalog #248-151AS

Hp	RPM	Tiltable belt	Catalog Number	List Price	Mult. Sym.	Shpg. Wgt.	Voltage	Style	Agency Approval	Notes
1/3	3600	Multi-Position	602E-MT	786	G1	24	115	Grinder/Belt Sander	—	g, n
1-1/2	3600	Fixed	2048-151D	1,582	G1	88	115/230	Belt Sander	UL	g
1-1/2	3600	Fixed	2048-153D	1,531	G1	76	208-230/460	Belt Sander	UL	h
1-1/2	3600	Three positions	248-151TD	1,733	G1	95	115/230	Belt Sander	UL	g
1-1/2	3600	Three positions	248-153TD	1,682	G1	84	208-230/460	Belt Sander	UL	h
1-1/2	3600	Three positions	248-181TD	2,037	G1	138	115/230	Grinder/Belt Sander	UR	J,I
1-1/2	3600	Three positions	248-183TD	1,979	G1	128	208-230/460	Grinder/Belt Sander	UL	h,I
1-1/2	0-3600	Three positions	248-151AS	1,867	G1	105	115	Adjustable Speed	UR	g,J,I

Industrial Buffers

Buffers are designed for use with soft cloth wheels **ONLY**. Specific buffing applications may require the addition of operator safety devices. Consult with a safety engineer before installation. Price includes flanges and nuts but **does not** include wheels.



Catalog #333B



Catalog #1458
with #GA20 Pedestal

Hp	RPM	Max. Wheel Size	Shaft Diameter	Catalog Number	List Price	Mult. Sym.	Shpg. Wgt.	Voltage	Agency Approval	Notes
1/4	1800	6"	1/2"	114	374	G1	24	115	UR	g
1/3	3600	6"	1/2"	111	374	G1	25	115	UR	g
3/4	1800	8"	3/4"	332B	735	G1	55	115/230	UR	g
3/4	3600	8"	3/4"	333B	735	G1	56	115/230	UR	g
3/4	1800	8"	3/4"	334B	718	G1	54	208-230/460	UR,CSA	h
3/4	3600	8"	3/4"	330B	718	G1	56	208-230/460	UR,CSA	h
1	1800	10"	7/8"	407B	975	G1	60	115/230	UR	j
1-1/2	3600	10"	7/8"	410B	959	G1	61	115/230	UR	j
1-1/2	1800	10"	7/8"	409B	936	G1	59	208-230/460	UR,CSA	h
1-1/2	3600	10"	7/8"	412B	936	G1	62	208-230/460	UR,CSA	h
2	1800	12"	1-1/4"	1250	2,260	G1	164	115/230	UR	k
2	3600	12"	1-1/4"	1251	2,195	G1	160	115/230	UR	k
3	1800	12"	1-1/4"	1252	2,075	G1	156	208-230/460	UR,CSA	k
3	3600	12"	1-1/4"	1253	2,016	G1	156	208-230/460	UR,CSA	k
5	1200	14"	1-1/4"	1457	3,029	G1	228	230	UR,CSA	m
5	1800	14"	1-1/4"	1458	2,579	G1	218	230	UR,CSA	m
7-1/2	1800	14"	1-1/4"	1454	2,880	G1	229	230	UR,CSA	m
7-1/2	3600	14"	1-1/4"	1453	2,725	G1	223	230	UR,CSA	m

NOTES:

- (g) Factory connected for 115 volts, power cord supplied.
- (h) Factory connected for 208-230 volts, no power cord.
- (J) Factory connected for 115 volts, no power cord.
- (k) Factory connected for 230, manual starter, specify voltage when ordering.
- (l) Supplied with 8"x1"x3/4" 36 grit wheel and 80 grit belt.
- (m) Factory connected for 230, magnetic starter must be changed for other voltages
- (n) Supplied with 0.014 wire wheel and 36" x 2" 100 grit belt